

LIGHT RIDER (September 2010)

FIXTURES

2 x 6-Bars Par 64 1000W
12 x Par 64 (1000W)
10 x Par 64 (1000W) Floorspots
20 x Par 56 (300W)
3 x 4-Bars Par 36 Pinspot (35W)
3 x Par 36 Pinspot (35W)
2 x Fresnel Griven Professional Spot 300/500 PCX (500W)
4 x Par 36 Audience Blinder (650W)
8 x Par 36 ACL (250W) (1 Set)
4 x Flood symmetrical (500W)
6 x Par 20 (50W)

4 x Strobe Sagitter DF Power 2500
12 x Martin Mac 300

DIMMER

2 x ETR Terra 12 x 2.3kW
1 x Lt Liberty 12 x 2.5kW
1 x Kotec LD1216 12 x 3,5kW (Spare)

CONTROLLER

AVOLITES pearl 2010
3 DMX 512 Lines from FOH to Stage

HAZER

1 LOOK, Unique 2

SCREEN

Rollscreen (fix installed behind FOH)
HKS Dolomit, 225 x 300 cm

BEAMER

NEC LT25, 2200 ansi, contrast 1500:1, projectionfactor 1.8 – 2.16:1
Max. resolution: 1400 x 1500px

NOTE

- MAX RISER SIZE 200 X 200 cm / 6.65 x 6.65 ft
- MAX BACKDROP SIZE ONLY 200 X 200 cm / 6.65 x 6.65 ft
(cause of ventilation support struts)

Additional power for tour lighting available *on request*:
CEE 32A, CEE 16A next to the stage.